



NOTES:
SPECIFICATION:

- CURRENT RATING: 3.0A MAX
- DIELECTRIC WITHSTAND VOLTAGE: 100VAC
- TEMPERATURE RANGE: -30 °C ~ 85 °C
- CONTACT RESISTANCE: 40 MILLIONHM MAX
- INSULATION RESISTANCE: 100 MEGOHMS MIN.
- INSERTION FORCE : 5N~20N
- UNMATING FORCE: 8N~20N
- DURABILITY:5000 CYCLES

H186- CF1WP03- X X X X X X

Electroplating	Metal Shell	Plastic material	Colour	Packing	Environmental protection
0=G/F	1=Copper Alloy	A=PBT	A=Black	A=Pe Bag	H=Halogen
2=3u"	2=Iron Alloy	B=PA66	L=Blue	B=Tube	R=ROHS
3=5u"	3=SUS	C=PA9T	W=White	C=Tray	D=Tape Reel
4=10u"		E=LCP	Y=Belge	E=Tape Reel+Mylar	
5=15u"					
6=30u"					



4	Shell1	1	SUS301 Ni Plating T=0.25mm	Ni:40~120u";
3	Housing2	1	LCP(G.F30%)	
2	Contact	5	Phosphor bronze C5210R-EH Au/Ni Plating T=0.20mm	Ni:40~160u"; Au:CONTACT AREA:3u", OTHER AREA:G/F
1	Housing	1	PA9T (G.F30%)	
ITEM	PART NAME	Q' TY	FINISH	NOTE

A5	CC1	B12	GND
A9	VBUS	B9	VBUS
A12	GND	B5	CC2
PIN	SIGNAL NAME	PIN	SIGNAL NAME

A0	RELEASED	Peng	25/03-20
REV	DESCRIPTION.	APPD.	Date

HULYN

深圳惠興力電子有限公司
SHEN ZHEN HUILY ELECTRONICS CO.,LTD.

FILE NOH186(Series)

TITLE
圖名

TYPE-C 6PIN 直立式防水母座

UNIT
單位

mm
inch

TOLERANCE(公差):
0.000 mm ± 0.10 mm
0.00 mm ± 0.25 mm
0.0 mm ± 0.30 mm

PART NO.
料號

H186-CF1WP03-23EBDR

SCALE
比例

1:1

DRAWN BY
製圖

Peng

DATE
日期

2020-03-25

REV.
版本

A.0

CHECKED BY
審核

Zhu

DATE
日期

2020-03-25

